



## Full Outdoor Green Signage BAA Series

Geephon manufactures displays for challenging outdoor environments, delivering exceptional performance with Mini LED backlighting for luminance ratings up to 6500 cd/m<sup>2</sup>. Our digital signage achieve incredibly bright imagery, even in intense sunlight and feature IP66 protection for increased durability.

BAA5522A-BB-35



### • Optimal Visual Clarity

- High-performance image processor
- Exceptional color expression with ultra-high resolution
- Offers adjustable picture quality and white balance



### • Outdoor Optimized High-Bright Display

- Achieves 3500 cd/m<sup>2</sup> for exceptional brightness
- Ensures excellent visibility in direct sunlight
- Smart light sensor for optimal brightness adjustment in all conditions
- Polarized sunglasses compatible



### • Enhanced Component Design

- Lightweight design for easy handling
- High-strength aluminum alloy for durability
- Modular components facilitate maintenance and replacement



### • Industry Top quality Heat Exchange Innovation

- Tailored for outdoor environments, featuring Geephon's proprietary heat sync patents
- Superior heat dissipation performance with no maintenance
- Significantly extends LCD product lifespan



### • Energy Metering and Protection Module

- Support the measuring of active energy
- Remote power on-off function
- Surge/lightning protection
- Carbon credits calculation function (optional)



### • Green Technology

- Features ultra-low power consumption.
- Achieves energy savings of up to 45%.



### • Local Dimming Innovation

- Implements LDM with 500+ individually controlled zones
- Achieves an ultra-high contrast ratio up to 250,000:1



### • CMS / Remote Management Support(optional)

- Cloud-based remote management (CetusMSC) and CMS platform (GalaxyASC) support
- Real-time monitoring of display status, including remote management and content distribution
- Remote control via PC and smart phone



### • Quiet Cooling System

- Incorporates a high-flux low-noise fan and intelligent algorithms to manage cooling
- Utilizes sensor data to optimize heat dissipation while minimizing noise levels
- Specially engineered for noise-reduced operation



### • Built-in Multiple Sensors


• Temperature sensor	• Shock sensor
• Humidity sensor	• Ambient light sensor
• Door opening sensor	• Pixel sensor (optional)

# Specifications

## Hardware Specifications

Panel	IPS
Display Size	55 inch
Protection Glass	IK10, AR High Permeability Glass
Protection Level	IP 66
Front Color	Black
Shell	Aluminum
Set Dimension (L*W*D)	1337.6 x 808.4 x 121.6mm
Bezel Width Width	63mm (L/R /H/V)
Active Display Area (H*V)	1209.6 x 680.4mm
Resolution	1080 x 1920
Type	MiniLED BLU
Brightness	4000 nits(Typ.), 3500 nits(Min.)
Contrast Ratio(Typ.)	350000:1
Viewing Angle(H/V)	178°(H) x 178°(V)(CR≥10)
Display Colors	16.7M
Color Gamut	72%
Response Time	6ms (Typ)
Operation Hour	24/7
Panel Orientation	Portrait
Smart Solution	PTC.DT1AHE-LAB
Connectivity	USB2.0*2, HDMI In*2, HDMI Out*1, Ethernet(RJ45)*2, RS232(RJ45)*1, Line Out*1
Power	Input Supply: 100-240V AC, 50/60Hz
Power Consumption	Max power: 345W Average power: (under IEC): 235W Max power with heating module: 1000W
Speaker	5W/8Ω *2
IR	Yes
Touch	Optional
Camera	Optional
Installation Methods	Floor Standing / Kiosk / Wall Mounting / Hanging / Single, Double
Package(W*H*D)	1488 x 960 x 262mm
Net Weight	84.4kg
Operating Temperature	-40°C ~ +50°C
Storage	-20°C ~ +60°C

## Dimensions



Unit: mm

## System Specifications

CPU	ARM Quad Core Cortex-A53 1.5G
GPU	Arm Mali-G52 2EE MC1
Operating System	Android 9
Screen Health	Smart Backlight Control - Yes
Remote Management	Smart Temperature Control - Yes Smart Fans Control - Yes Smart Monitoring System Cloud - Yes/CetusMSC Overheating Protection - Yes
Cloud Advertising	Optional
Distribution System	Optional
Cloud Splice System	Optional
Memory	DDR 2G
Storage	EMMC 16GB Ethemnet (RJ45)
Ethernet	WiFi 802.11b/g/n 4G LTE(FDD/TDD) (Optional)
Video Decoder	MPEG-1/2/4,H.264,HEVC,VP8,VP9,AVS+,AVS2,AV1
Audio Decoder	MPEG-1,MPEG-2(layerI/II) MP3,AAC-LC,HE-AAC
Picture Decoding	JPG,JPEG,PNG,BMP

## What's in the box

Remote Controller	x 1
RS232 Adaptor	x 1
Door Key	x 1

## Warranty

Warranty	Three years or by contract
----------	----------------------------

\* Compatibility may differ by equipment.

\* Software compatibility may change over time. Please contact your regional sales representative for details.

\* Specifications are subject to change without notice, please contact sales to verify.